

FICHA TÉCNICA PORTA PALETES

Characteristics	Manufacturer	Unit	JAC
	Model		CBD15
	Power unit		electric
	Operation		Walking type
	Rated traction weight	Q (t)	1,5
	Load center	c (mm)	600
	Axle centre to fork face	x (mm)	944
	Wheel base	y (mm)	1243
Weights	Service weight (with battery)	kg	150
Wheels/Tyres	Wheels type		PU
	Driving wheel size	$\Phi \times w$ (mm)	210×70
	Bearing wheel size	$\Phi \times w$ (mm)	80×60
	Wheels, number front/rear (x = driven)		1x/4
	Track width	b ₁₁ (mm)	400/535
Dimensions	Lift	h ₃ (mm)	200
	Overall height(With handle lowered henght)	h ₁₄ (mm)	740/1160
		h ₁₃ (mm)	85
	Overall length	l ₁ (mm)	1603
	Length to fork face	l ₂ (mm)	453
	Overall width	b ₁ / b ₂ (mm)	550/685
	Fork dimensions	s/e/l (mm)	50/150/1150
	Width of forks	b ₅ (mm)	550
	Min.Ground clearance	m ₂ (mm)	35
	Aisle width with pallet 1000 x 1200 across forks	Ast (mm)	1804
	Aisle width with pallet 800 x 1200 along forks	Ast (mm)	1854
	Min.Turning radius	Wa (mm)	1398
Performance	Travel speed,laden/unladen	km/h	4.2/4.5
	Maximum climbing ability, with/without load	(%)	5/10
	Service brake		电磁制动
Drive	Drive motor, 60 minute rating	kW	0,75
	Lift motor rating at S3 15%	kW	0,8
	Battery according to DIN 43531/35/36 A,B,C,no		no
	Battery voltage/rated capacity	V/Ah	24/30
	Battery weight (± 5%)	kg	7,8
Others	Type of drive control		DC
	Noise level at operator's ear	dB(A)	≤70
			mechanical steering