

FICHA TÉCNICA STACKER ELÉTRICO TRIPLEX COM PLATAFORMA

Model	CDD15 triplex with platform	CDD20 triplex with platform
Load capacity (kg)	1500	2000
Load capacity on Max. height(kg)	700	800
The max. lifting height(mm)	4600	4600
Load center distance(mm)	600	600
Fork length(mm)	1150	1150
Single fork width(mm)	180	180
Overall fork width(mm)	695	695
Lowered fork height(mm)	86	86
Fixed leg length(mm)	875	875
Single fixed leg width(mm)	124	124
Inside width between fixed legs(mm)	391	391
Outside width between fixed legs(mm)	639	639
Aisle width for pallets 1000×1200 cross ways	2458	2458
Aisle width for pallets 800×1200 length ways	2398	2398
Turning radius(mm)	1620	1620
Front wheel size, number	80×70 4	80×70 4
Driving wheel size, number	250×80 1	250×80 1
Balance wheel size, number	150×58 2	150×58 2
Overalllength(with Pedal)(mm)	1984 (2384)	1984 (2384)
Overall width(mm)	1050	1050
Extended mast height(mm)	5100	5100
Lowered mast height (mm)	2098	2098
Battery voltage(dimensions)mm	24V/280Ah (1010/212/465)	24V/280AH (1010/212/465)
The charger	24V/40A	24V/40A
Lifting Motor	Lift speed: 116/74mm, Lowering speed: 104/95mm/s (laden/unladen)	3,0kw. Lift speed: 116/74mm/s, Lowering speed: 104/95mm/s (laden/unladen)
Driving Motor	Driving speed: 5.5/5.2km/h (laden/unladen)	1,5kw. Driving speed: 4.8/3.4km/h (laden/unladen)
Working time of fully charged batteries (h)	5	5
Service Weight(kg)	1410	1420